

CCD

USE

Ideal for engineering teams, capable of cutting sheets steel 8 to 40 mm thick.

These charges have amply demonstrated their effectiveness also in the field of ammunition deactivation.

CHARACTERISTICS

- Safe handling and easy initiation.
- Included an adequate support system adaptable to most scenarios.
- Longitudinally interlinkable between them.
- Highly effective in proportion to the small amount of explosive contained.



TECHNICAL CHARACTERISTICS

| CCD | Dimensions (mm) | Explosive HWC (g) | Deep cutting (mm) | Stand-off (mm) |
|-----|-----------------|-------------------|-------------------|----------------|
| 10 | 146x20x17 | 20 | 8 | 10 |
| 15 | 146x25x24 | 45 | 12 | 15 |
| 20 | 148x30x30 | 80 | 16 | 20 |
| 25 | 148x35x37 | 125 | 20 | 25 |
| 30 | 148x43x40 | 181 | 25 | 30 |
| 50 | 154x68x64 | 521 | 40 | 50 |

PRESENTATION OF THE PRODUCT

| CCD | Packing (un) | Complete packaging weight (mm) | Packaging dimensions (mm) |
|-----|--------------|--------------------------------|---------------------------|
| 10 | 70 | 11 | 542x403x176 |
| 15 | 70 | 12 | |
| 20 | 70 | 18 | |
| 25 | 50 | 22 | |
| 30 | 50 | 24 | |
| 50 | 24 | 24 | |

TEMPERATURE LIMITS

Uso y almacenamiento (°C)..... -30 / +52